## LEED Green Associate Activity #5 – Water Efficiency (WE)

Before completing this Activity Read: GA02 - Pgs. 257-258 & GA09 – Pgs. 51-63 (see lorisweb.com)

Note the following abbreviations are used in this activity:

- NC LEED BD+C: New Construction and Major Renovation
- CS LEED BD+C: Core and Shell Development
- S LEED BD+C: Schools
- R LEED BD+C: Retail
- DC LEED BD+C: Data Centers
- WDC LEED BD+C: Warehouses and Distribution Centers
- HOS LEED BD+C: Hospitality
- HC LEED BD+C: Healthcare

Although the LEED BD+C reference guide does not number the LEED prerequisites and credits, for this exercise they have been numbered in the order presented in the credit category.

## Fill-In, Multiple Choice, Matching

1. Test your knowledge of how well you know the names of the credits for the Water Efficiency (WE) credit category:

LEED B	LEED BD+C: NC, CS, S, R, DC, WDC, HOS, HC		
Credit	Name		
P1			
P2			
Р3			
C1			
C2			
C3			
C4			

## 2. Match the intent shown below to the prerequisite or credit:

## LEED BD+C: NC, CS, S, R, DC, WDC, HOS, HC

Credit	ANS	Credit	ANS	
WE – P1		WE – C1		
WE – P2		WE – C2		
WE – P3		WE – C3		
		WE – C4		

	INTENT
А	To conserve water used for cooling tower makeup while controlling microbes, corrosion, and scale in
	the condenser water system.
В	To reduce indoor water consumption.
С	To reduce outdoor water consumption.
D	To support water management and identify opportunities for additional water savings by tracking
	water consumption.

- 3. List the four areas of water use that are addressed by the Water Efficiency (WE) credits:
  - 1.
  - 2.
  - --
  - 3. 4.
- 4. The conservation and creative reuse of water are important because only \_\_\_\_\_\_ of Earth's water is fresh water, and of that, slightly over \_\_\_\_\_\_\_ is trapped in glaciers.
- 5. In the U.S., buildings account for \_\_\_\_\_\_ of potable water use, the third-largest category, behind thermoelectric power and irrigation.
- Designers and builders can construct green buildings that use significantly less water than conventional construction by incorporating \_\_\_\_\_\_ landscapes that eliminate the need for \_\_\_\_\_\_, installing water efficient \_\_\_\_\_\_, and reusing \_\_\_\_\_\_, for nonpotable water needs.

OPTION 1. \_\_\_\_\_ Irrigation Required Show that the landscape does not require a \_\_\_\_\_\_ irrigation system beyond a maximum \_\_\_\_\_\_ establishment period.

OR

OPTION 2. \_\_\_\_\_\_ Irrigation Reduce the project's landscape water requirement by at least \_\_\_\_\_\_ from the calculated baseline for the site's \_\_\_\_\_\_ watering month. Reductions must be achieved through plant \_\_\_\_\_\_ selection and irrigation system \_\_\_\_\_\_, as calculated by the Environmental Protection Agency (EPA)

 WE Prerequisite Indoor Water use Reduction requirements: Building Water Use For the fixtures and fittings listed in Table 1, as applicable to the project scope, reduce aggregate water consumption by \_\_\_\_\_\_ from the baseline. Base calculations on the volumes and flow rates shown in Table 1.

All newly installed _	,,,	lavatory faucets, and
	that are eligible for labeling must be	labeled
(or a local equivalen	t for projects outside the U.S.).	

#### Complete Table 1. Baseline water consumption of fixtures and fittings:

Table 1. Baseline water consumption of fixtures and fittings **Fixture or fitting Baseline (IP units)** Baseline (SI units) Toilet (water closet)\* 6 lpf Urinal\* 3.8 l[f at 60 psi all others 1.9 lpm at 415 kPa, all others Public lavatory (restroom) faucet except private applications except private applications Private lavatory faucet at 60 psi 8.3 lpm at 415 kPa Kitchen faucet (excluding faucets used exclusively for filling 8.3 lpm at 415 kPa at 60 psi operations) 9.5 lpm at 550 kPa per shower at 80 psi per Showerhead\* shower stall stall

gpf	=
gpm	=
psi	=

Appliance and Process Water Use

Install \_\_\_\_\_\_, \_\_\_\_\_, and \_\_\_\_\_\_, within the project scope that meet the requirements listed in the tables below.

#### Complete Table 2. Standards for appliances

Table 2. Standards for appliances		
Appliance	Requirement	
Residential Clothes Washer	or performance equivalent	
Commercial Clothes Washer		
Residential Dishwasher (standard and compact)	or performance equivalent	
Prerinse spray valve		
Ice machine	or performance equivalent and use either air-cooled or closed-loop cooling, such as chilled or condenser water system	

## Complete Table 3. Standards for processes

Table 3. Standards for processes			
Process	Requirement		
Heat rejection and cooling	Nothrough cooling with potable water for any equipment or appliances that reject heat		
Cooling towers and evaporative condensers	Equip with <ul> <li>makeup water</li> <li>conductivity controllers and overflow</li> <li>efficient drift eliminators that reduce drift to maximum of of recirculated water volume for counterflow towers and of recirculated water flow for cross-flow towers</li> </ul>		

gpm = gallons per minute lpm = liters per minute

Healthcare, Retail, Schools, and Hospitality Only

In addition, water-consuming appliances, equipment, and processes must meet the requirements listed in Tables 4 and 5.

# Complete Table 4. Standards for appliances

Table 4. Standards for appliances				
Kitchen e	quipment	Requirement (IP units)	Requirements (SI units)	
	Undercounter	≤ 1.6 gal/rack	≤ 6.0 liters/rack	
	Stationary, single tank, door	≤ 1.4 gal/rack	≤ 5.3 liters/rack	
	Single tank, conveyor		≤ 3.8 liters/rack	
	Multiple tank, conveyor	≤ 0.9 gal/rack	≤ 3.4 liters/rack	
	Flight machine	≤ 180 gal/hour	≤ 680 liters/hour	
	Batch	≤ 6 gal/hour/pan	≤ 23 liters/hour/pan	
	Cook-to-order	≤ 10 gal/hour/pan	≤ 38 liters/hour/pan	
	Countertop or stand	≤ 3.5 gal/hour/pan	≤ 13 liters/hour/pan	
	Roll-in	≤ 3.5 gal/hour/pan	≤ 13 liters/hour/pan	

Complete Table 5. Process requirements

Table 5. Process requirements		
Process	Requirement	
	Where local requirements limit discharge temperature of fluids into drainage system, use tempering device that runs water only when equipment discharges hot water OR Provide thermal recovery heat exchanger that cools drained discharge water below code-required maximum discharge temperatures while simultaneously preheating inlet makeup water OR If fluid is steam condensate, return it to boiler	
	Use no device that generates vacuum by means of water flow through device into drain	

The \_\_\_\_\_\_ label was developed by the U.S. Environmental Protection Agency to identify these efficient fixtures and ensure that higher efficiency does not come at the cost of performance.

- 9. List the fixtures that the WaterSense label can be found for:
  - 1.
  - 2.
  - 3.
  - 4.

10. List the fixture types that are not labeled by WaterSense:

- 1.
- 2.
- 3.
- 4.
- 11. WE Prerequisite Building-Level Water Metering requirements:

Building Water Use

Install \_\_\_\_\_\_ water meters that measure the \_\_\_\_\_\_ potable water use for the building and associated grounds. Meter data must be compiled into \_\_\_\_\_\_ and annual summaries; meter \_\_\_\_\_\_ can be manual or automated.

Commit to \_\_\_\_\_\_ with USGBC the resulting whole-project water usage data for a \_\_\_\_\_\_-year period beginning on the date the project accepts LEED certification or typical occupancy, whichever comes first.

This commitment must carry forward for \_\_\_\_\_\_ years or until the building changes ownership or lessee.

12. WE Credit Outdoor Water Use Reduction requirements:

Reduce outdoor water use through one of the following options. Nonvegetated surfaces, such as permeable or impermeable pavement, should be \_\_\_\_\_\_ from landscape area calculations. Athletic fields and \_\_\_\_\_\_ (if vegetated) and food \_\_\_\_\_\_ may be included or excluded at the project team's discretion.

Option 1. No Irrigation Required (2 points except Healthcare, 1 point Healthcare) Show that the landscape does not require a \_\_\_\_\_\_ irrigation system beyond a maximum \_\_\_\_\_\_-year establishment period.

OR

Option 2. Reduced Irrigation (2 points except Healthcare, 1 point Healthcare) Reduce the project's landscape water requirement (LWR) by at least \_\_\_\_\_\_ from the calculated baseline for the site's \_\_\_\_\_\_ watering month. Reductions must first be achieved through plant \_\_\_\_\_\_ selection and irrigation system \_\_\_\_\_\_ as calculated in the Environmental Protection Agency (EPA) WaterSense Water Budget Tool. Additional reductions beyond \_\_\_\_\_\_ may be achieved using any combination of efficiency, alternative water sources, and smart scheduling technologies.

# 13. Complete Table 1. Points for reducing irrigation water

Table 1. Points for reducing irrigation water

Percentage reduction from baseline	Points (except HC)	Points (HC)

14. WE Credit Indoor Water Use Reduction requirements:

Further reduce fixture and fitting water use from the calculated \_\_\_\_\_\_\_ in WE Prerequisite Indoor Water Use Reduction. Additional potable water savings can be earned above the prerequisite level using \_\_\_\_\_\_ water sources. Include fixtures and fittings necessary to meet the needs of the occupants. Some of these fittings and fixtures may be outside the project boundary. Points are awarded according to Table 1.

Complete Table 1. Points for reducing water use

Table 1. Points for reducing water use					
Percentage reduction Points (NC, CS, DC, WDC) Points (S, R, HOS, HC)					

AND

Appliance and Process Water

Install equipment within the project scope that meets the minimum requirements in Table 2, 3, 4, or 5. \_\_\_\_\_\_ point is awarded for meeting all applicable requirements in any \_\_\_\_\_\_ table. All applicable

equipment listed in each table must meet the standard.

Schools, Retail, and Healthcare projects can earn a \_\_\_\_\_\_ point for meeting the requirements of \_\_\_\_\_\_ tables. To use Table 2, the project must process at least \_\_\_\_\_\_ lbs (57 606 kg) of laundry per year.

Complete Table 2. Compliant commercial washing machines

Table 2. Compliant commercial washing machines

Washing machine	Requirements (IP)		Requirements (SI)	
On-premise, minimum capacity 2,400	Maximum	gals per	Maximum	liters per
lbs (1088 kg) per 8-hour shift	pound*		0.45 kilograms*	

\* Based on equal quantities of heavy, medium, and light soil laundry.

To use Table 3, the project must serve at least \_\_\_\_\_ meals per day of operation. All process and appliance equipment listed in the category of kitchen equipment and present on the project must comply with the standards.

Complete Table 3. Standards for commercial kitchen equipment

Table 3. Standards for commercial kitchen equipment

Kitchen equipment	Requirement (IP units)	Requirements (SI units)
Undercounter	ENERGY STAR	ENERGY STAR or performance equivalent
Stationary, single tank, door	ENERGY STAR	ENERGY STAR or performance equivalent
Single tank, conveyor	ENERGY STAR	ENERGY STAR or performance equivalent
Multiple tank, conveyor	ENERGY STAR	ENERGY STAR or performance equivalent
Flight machine	ENERGY STAR	ENERGY STAR or performance equivalent
Batch (no drain connection)	≤ 6 gal/hour/pan	≤ 23 liters/hour/pan
Cook-to-order (with drain connection)	≤ 10 gal/hour/pan	≤ 38 liters/hour/pan
Countertop or stand	≤ 3.5 gal/hour/pan	≤ 13 liters/hour/pan
Roll-in	≤ 3.5 gal/hour/pan	≤ 13 liters/hour/pan
Disposer	3-8 gpm, full load condition, 10 minute automatic shutoff; or 1 gpm, no-load condition	11–30 lpm, full load condition, 10-min automatic shutoff; or

		43.8 lpm, no-load
		condition
Scrap collector	Maximum 2 gpm	Maximum 7.6 lpm
	makeup water	makeup water
Pulper	Maximum 2 gpm	Maximum 7.6 lpm
	makeup water	makeup water
Strainer basket	No additional water	No additional water
	usage	usage

Complete Table 4. Compliant laboratory and medical equipment

Table 4. Compliant laboratory and medical equipment			
Lab equipment	Requirement (IP)	Requirements (SI)	
Reverse-osmosis water purifier	recovery	recovery	
Steam sterilizer	For 60-inch sterilizer, gal/U.S. tray For 48-inch sterilizer, gal/U.S. tray	For 1520-mm sterilizer, 28.5 liters/DIN tray For 1220-mm sterilizer, 28.35 liters/DIN tray	
Sterile process washer	gal/US tray	1.3 liters/DIN tray	
X-ray processor, 150 mm or more in any dimension	processor water recycling unit		
Digital imager, all sizes			

To use Table 5, the project must be connected to a municipal or district steam system that does not allow the return of steam condensate.

Complete Table 5. Compliant municipal steam systems

Table 5. Compliant municipal steam systems		
Steam system	Standard	
Steam condensate disposal	municipally supplied steam condensate (no return) to drainage system with heat recovery system or reclaimed water	
OR		
Reclaim and use steam condensate	recovery and reuse	

15. WE Credit Indoor Water Use Reduction exemplary performance is earned if the project achieves a \_\_\_\_\_\_ water use reduction.

 WE Credit Cooling Tower Water Use requirements: For cooling towers and evaporative condensers, conduct a one-time \_\_\_\_\_\_ water analysis, measuring at least the \_\_\_\_\_\_ control parameters listed in Table 1.

# 17. Complete Table 1. Maximum concentrations for parameters in condenser water

Table 1. Maximum concentrations for parameters in condenser water		
Parameter	Maximum level	

ppm = parts per million

µS/cm = micro siemens per centimeter

Calculate the number of cooling tower \_\_\_\_\_\_ by dividing the maximum allowed concentration level of each parameter by the actual concentration level of each parameter found in the potable makeup water. \_\_\_\_\_\_ cooling tower cycles to avoid exceeding maximum values for any of these parameters.

Complete Table 2. Points for cooling tower cycles

Table 2. Points for cooling tower cycles		
Parameter	Points	
Maximum number of cycles achieved without exceeding any		
filtration levels or affecting operation of condenser water system		
(up to maximum of 10 cycles)		
Achieve a minimum 10 cycles by increasing the level of treatment in		
condenser or make-up water		
OR		
Meet the minimum number of cycles to earn 1 point and use a		
minimum 20% recycled nonpotable water		

18. WE Credit Water Metering requirements:

Install \_\_\_\_\_\_ water meters for \_\_\_\_\_ or more of the following water subsystems, as applicable to the project:

\_\_\_\_\_\_. Meter water systems serving at least \_\_\_\_\_\_ of the irrigated landscaped area. Calculate the percentage of irrigated landscape area served as the total metered irrigated landscape area divided by the total irrigated landscape area. Landscape areas fully covered with \_\_\_\_\_\_ or \_\_\_\_\_\_ vegetation that requires no routine irrigation may be \_\_\_\_\_\_ from the calculation.

\_\_\_\_\_. Meter water systems serving at least \_\_\_\_\_\_ of the indoor fixtures and fitting described in WE Prerequisite Indoor Water Use Reduction, either directly or by deducting all other measured water use from the measured total water consumption of the building and grounds.

\_\_\_\_\_. Meter water use of at least \_\_\_\_\_ of the

installed domestic hot water heating capacity (including both tanks and on-demand heaters). Boiler with aggregate projected annual water use of \_\_\_\_\_\_ gallons (378 500 liters) or more, or boiler of more than BtuH (150 kW). A single makeup meter may record flows for multiple boilers.

. Meter reclaimed water, regardless of rate. A reclaimed water system with a makeup water connection must also be metered so that the true reclaimed water component can be determined.

\_\_\_\_\_\_. Meter at least \_\_\_\_\_\_ of expected daily water consumption for process end uses, such as humidification systems, dishwashers, clothes washers, pools, and other subsystems using \_\_\_\_\_ water.

Healthcare Projects only

In addition to the requirements above, install water meters in any \_\_\_\_\_\_ of the following: \_\_\_\_\_ water systems (reverse-osmosis, de-ionized); backwash water; water use in \_\_\_\_\_\_department; water use in \_\_\_\_\_; water use in \_\_\_\_\_; water use in central \_\_\_\_\_\_and processing department; water use in physiotherapy and \_\_\_\_\_ and treatment areas; water use in \_\_\_\_\_\_suite; \_\_\_\_\_ hydronic system makeup water; and makeup for domestic hot water systems.