



PROJECT NO.
2007

SCALE
NTS
DATE
06/01/07

DRAWING NO.
E6.1

LIGHT FIXTURE SCHEDULE

FIXTURE TYPE	DESCRIPTION	VOLTAGE	LAMPS	MANUF. & CATALOG #	FIXTURE TYPE	DESCRIPTION	VOLTAGE	LAMPS	MANUF. & CATALOG #
"A"	2'x4' FLUORESCENT LAY-IN LIGHT FIXTURE, 4-LAMP, 3" DEEP (18) CELL PARABOLIC SPECULAR LOUVER, COLD ROLLED STEEL HOUSING AND DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(4) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # 2EP3GAX-432S36I-277V-L8735-EB81-U	"J1"	SAME AS TYPE "J" EXCEPT 36" IN LENGTH.	277	(2) 26 WATT (FLUOR.) (F26T8/35K)	COOPER # SNL-226-277V-EL4-EB81-U
"A1"	2'x4' FLUORESCENT LAY-IN LIGHT FIXTURE, 3-LAMP, 3" DEEP (18) CELL PARABOLIC SPECULAR LOUVER, COLD ROLLED STEEL HOUSING AND DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(3) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # 2EP3GAX-332S36I-277V-L8735-EB81-U	"K"	2'x4' FLUORESCENT LAY-IN LIGHT FIXTURE, 4-LAMP, .125" PRISMATIC LENSE, COLD ROLLED STEEL HOUSING, EXTRUDED ALUMINUM DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(4) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # 2GC-XF-432A125-277V-L8735-EB81-U
"A2"	2'x4' FLUORESCENT LAY-IN LIGHT FIXTURE, 2-LAMP, 3" DEEP (18) CELL PARABOLIC SPECULAR LOUVER, COLD ROLLED STEEL HOUSING AND DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(2) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # 2EP3GAX-232S36I-277V-L8735-EB81-U	"M"	METAL HALIDE WALL PACK LIGHT FIXTURE, DIE-CAST ALUMINUM ONE-PIECE HOUSING AND DOOR FRAME, CLEAR, PRISMATIC LENS, WIDE FLOOD DISTRIBUTION, POWDER COAT FINISH (COLOR BY ARCH.), FULLY GASKETED, WET LOCATION LISTED. PROVIDE WITH COLD WEATHER MULTI-TAP HPF BALLAST.	277	(1) 175 WATT (M.H.)	COOPER # MHCW-175H-277-MT-LL
"B"	2'x2' FLUORESCENT LAY-IN LIGHT FIXTURE, 2-LAMP, 3" DEEP (9) CELL PARABOLIC SPECULAR LOUVER, COLD ROLLED STEEL HOUSING AND DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(2) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # 2EP3GAX-232S36I-277V-L8735-EB81-U	"S"	METAL HALIDE BOLLARD LIGHT FIXTURE, DIE-CAST ALUMINUM ONE-PIECE HOUSING, CLEAR, POLYCARBONATE LENS, POWDER COAT FINISH (COLOR BY ARCH.), FULLY GASKETED, WET LOCATION LISTED. PROVIDE WITH COLD WEATHER MULTI-TAP HPF BALLAST.	277	(1) 50 WATT (M.H.)	GREENLEE # ABS-50MH-MT-277V-EL-BLK-PT
"C"	6"Ø RECESSED COMPACT FLUORESCENT DOWNLIGHT, 5 11/16" APERTURE, SPECULAR CLEAR LOW IRIDESCENT REFLECTOR, WHITE POLYMER TRIM RING, INSTANT START ELECTRONIC BALLAST.	277	(1) 32W TRIPLE (COMP. FLUOR.) (4-PIN/35K)	COOPER # C60321E-6050LI-277V	"S1"	SINGLE HEAD AREA LUMINAIRE (RECTANGULAR), ONE-PIECE DIE-CAST HOUSING AND DOOR FRAME, CLEAR GLASS LENS, HYDROFORMED ALUMINUM REFLECTOR (TYPE III DISTRIBUTION), BLACK POWDER COAT FINISH, FULLY GASKETED, U.L. LISTED WET LOCATION. PROVIDE WITH MOUNTING ARM, HORIZONTAL LAMP, MOUNTED ON A 25' BLACK ROUND TAPERED STEEL POLE ON A 3' ABOVE GRADE CONCRETE BASE. CONNECT AT 277 VOLTS.	277	(1) 400 WATT (Mogul Base M.H.)	FIXTURE: COOPER # MHHR-R3-400MH-MT-277V-BLK-M59PJ-400/UFG w/OA1064C001 POLE: COOPER # RTS8A30SYM1
"C1"	5 3/4"Ø RECESSED INCANDESCENT DOWNLIGHT, 4 7/16" APERTURE, SPECULAR CLEAR LOW IRIDESCENT REFLECTOR, WHITE POLYMER TRIM RING.	120	(1) 100W (INC.)	COOPER # HD4-4510LI-120V	"S2"	SAME AS TYPE "S1" EXCEPT w/ (2) HEAD CONFIGURATION (180° ORIENTATION/SEPARATION).	277	(2) 400 WATT (Mogul Base M.H.)	FIXTURE: COOPER # MHHR-R3-400MH-MT-277V-BLK-M59PJ-400/UFG w/OA1064C002 POLE: COOPER # RTS8A30SYM2
"C2"	5"Ø RECESSED INCANDESCENT LOW VOLTAGE DOWNLIGHT, 1 7/8" OPEN COILEX APERTURE, BLACK BAFFLE, WHITE POLYMER TRIM RING, DUAL TAP INTEGRAL MAGNETIC STEP-DOWN TRANSFORMER (120V TO 12V).	120	(1) 75W (MR16 INC.)	COOPER # H1499T75-1419-120V-P	"X"	SINGLE FACE UNIVERSAL MOUNTED "LED" EXIT SIGN, CAST ALUMINUM HOUSING AND DOOR FRAME, RED LETTERS AND CHEVRONS, DIRECTIONAL CHEVRON ARROWS AS INDICATED ON DWGS., INSTANT START EMERGENCY BALLAST.	277	INCLUDED (LED)	COOPER # CX-7-1-70-R-D-277V
"D"	8"Ø RECESSED METAL HALIDE DOWNLIGHT, 8 1/2" APERTURE, SPECULAR CLEAR LOW IRIDESCENT REFLECTOR, BLACK BAFFLE AND WHITE TRIM RING, HPF BALLAST.	277	(1) 70W (M.H.)	COOPER # M6024T-740-10002P-MP100/U/MED-277V	"X2"	DOUBLE FACE UNIVERSAL MOUNTED "LED" EXIT SIGN, CAST ALUMINUM HOUSING AND DOOR FRAME, RED LETTERS AND CHEVRONS, DIRECTIONAL CHEVRON ARROWS AS INDICATED ON DWGS., INSTANT START EMERGENCY BALLAST.	277	INCLUDED (LED)	COOPER # CX-7-2-70-R-D-277V
"F"	1'x4' SUSPENDED STRIP FLUORESCENT LIGHT FIXTURE, 2-LAMP, COLD ROLLED STEEL HOUSING, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST. PROVIDE w/ CHAIN SET AND WIRE GUARD.	277	(2) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # SS-232-277V-EB81-LI w/ AYC-CHAIN/SET-U & WG/SS-4FT-U	"Y"	4 1/2" SURFACE INCANDESCENT SINGLE HEAD LUMINAIRE <RECTANGULAR> ONE-PIECE THERMOPLASTIC HOUSING, WHITE FINISH, C/W BATTERY.	277	(1) 4V BI-PIN HALOGEN LAMP	COOPER # MML
"G"	WALL MOUNTED INCANDESCENT ELEVATOR PIT LIGHT FIXTURE, MATTE BLACK FINISH, 120V., U.L. LISTED FOR WET LOCATION. PROVIDE w/ OPAL GLASS CYLINDER LENS AND WIRE GUARD.	120	(1) 100W A19 (INCAND.)	HALO # H2411-MB-120V w/WG11					
"H"	8"x48" FLUORESCENT SURFACE MOUNTED LIGHT FIXTURE, 2-LAMP, CLEAR ACRYLIC PRISMATIC LENS, COLD ROLLED STEEL HOUSING AND DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(2) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # BI-232-277V-EB81-U					
"J"	2 3/4"x48" NARROW STAGGERED FLUORESCENT SURFACE MOUNTED LIGHT FIXTURE, 2-LAMP, COLD ROLLED STEEL HOUSING AND DOOR, BAKED WHITE POWDER ENAMEL FINISH, INSTANT START ELECTRONIC BALLAST.	277	(2) 32 WATT (FLUOR.) (F32T8/35K)	COOPER # SNL-232-277V-EB81-U					

ELECTRICAL - LIGHT FIXTURE SCHEDULE
NO SCALE